

**IN THE CLAIMS**

Please amend the claims as follows.

1. (Currently Amended) For use in a wireless network, a distributed architecture for the reception of signals transmitted from one or more mobile stations, comprising:

a plurality of base transceiver stations for receiving said signals;

a Code Division Multiple Access (CDMA) detector in each said base transceiver station; and

a combiner in each said base transceiver station for combining a first signal received from a first mobile station by a target ~~Base~~ base transceiver station with signals ~~transmitted sent~~ sent to said target base transceiver station by non-target ones of said plurality of base transceiver stations.

2-4. (Canceled)

5. (Currently Amended) The distributed architecture as set forth in Claim 1 further comprising an error detector in each said base transceiver station for determining the error count when said first signal received from said first mobile station and ~~encoded second signals, received from non-target~~ said signals sent to said target base transceiver station by said non-target base transceiver stations are combined.

6. (Currently Amended) The distributed architecture as set forth in Claim [[1]] 5, further comprising a reverse link power control for notifying said mobile station to increase power if error count is high.

7. (Currently Amended) The distributed architecture as set forth in Claim [[1]] 5, further comprising a reverse link power control for notifying said mobile station to decrease power if error count is low.

8. (Currently Amended) A wireless office network, comprising:  
a mobile switching center;  
a plurality of ~~Base Stations~~ base stations each comprising a base station controller and at least one base transceiver station;  
a backhaul network for connecting said mobile switching center with each said ~~Base Station Subsystem~~ base station; and  
a distributed architecture for the reception of signals transmitted from one or more mobile stations, comprising:  
a plurality of base transceiver stations for receiving said signals;  
a Code Division Multiple Access (CDMA) detector in each of said plurality of base transceiver stations; and

a combiner in each said base transceiver station for combining a first signal received from a first mobile station by a target base transceiver station with signals ~~transmitted~~ sent to said target base transceiver station by non-target ones of said plurality of ~~said non-target~~ base transceiver stations.

9-11. (Canceled)

12. (Currently Amended) The wireless office network as set forth in Claim 8 further comprising an error detector in each said base transceiver station for determining the error count when said first signal received from said first mobile station and ~~encoded second signals, received from non-target base~~ said signals sent to said target base transceiver station by said non-target base transceiver stations~~[[,]]~~ are combined.

13. (Currently Amended) The wireless office network as set forth in Claim ~~[[8]]~~ 12, further comprising a reverse link power control for notifying said mobile station to increase power if error count is high.

14. (Currently Amended) The wireless office network as set forth in Claim ~~[[8]]~~ 12, further comprising a reverse link power control for notifying said mobile station to decrease power if error count is low.

15. (Currently Amended) For use in a wireless network, a method for receiving signals transmitted from one or more mobile stations, comprising the steps of:

detecting a baseband signal from a mobile station at a plurality of base transceiver stations, one station being a target base transceiver station;

producing a symbol based on a detector output determined from said baseband signal received at each non-target base transceiver station;

combining said non-target base transceiver station symbols with said baseband signal received at said target base transceiver station ~~symbol~~; and

sending a power adjustment signal to said mobile station.

16. (Original) The method as set forth in Claim 15, further comprising the step of:  
sending a code pattern for said mobile station to each non-target base transceiver station in said network.

17. (Original) The method as set forth in Claim 15, further comprising the step of:  
sending said symbol from each said non-target base transceiver station to said target base transceiver station.

18. (Original) The method as set forth in Claim 15, further comprising:  
decoding said symbols received from each said non-target base transceiver station.
19. (Original) The method as set forth in Claim 15, further comprising:  
responsive to a high error count, prompting said mobile station to increase power.
20. (Original) The method as set forth in Claim 15, further comprising the step of:  
responsive to a low error count, prompting said mobile station to decrease power.
21. (New) For use in a wireless network comprising a plurality of base transceiver stations capable of communicating with mobile stations accessing said wireless network, a first base transceiver station comprising:  
a Code Division Multiple Access (CDMA) detector capable of receiving first CDMA signals transmitted by a first one of said mobile stations; and  
a combiner capable of combining said first CDMA signals with second CDMA signals sent to said first base transceiver station from a second base transceiver station.
22. (New) The first base transceiver station as set forth in Claim 21, further comprising an error detector capable of receiving a combined output signal from said combiner and outputting an error value corresponding to a number of errors detected in said combined output signal.

23. (New) The first base transceiver station as set forth in Claim 22, further comprising power control circuitry capable of receiving said error value from said error detector and generating a power adjustment signal for transmission to said first mobile station.

24. (New) The first base transceiver station as set forth in Claim 23, wherein said power control circuitry compares said error value to a threshold value and determines said power adjustment signal based on said comparison.

25. (New) A wireless network comprising:  
a plurality of base transceiver stations capable of communicating with mobile stations accessing said wireless network, wherein a first one of said plurality of base transceiver stations comprises:

a Code Division Multiple Access (CDMA) detector capable of receiving first CDMA signals transmitted by a first one of said mobile stations; and

a combiner capable of combining said first CDMA signals with second CDMA signals sent to said first base transceiver station from a second one of said plurality of base transceiver stations.

26. (New) The wireless network as set forth in Claim 25, further comprising an error detector capable of receiving a combined output signal from said combiner and outputting an error value corresponding to a number of errors detected in said combined output signal.

27. (New) The wireless network as set forth in Claim 26, further comprising power control circuitry capable of receiving said error value from said error detector and generating a power adjustment signal for transmission to said first mobile station.

28. (New) The wireless network as set forth in Claim 27, wherein said power control circuitry compares said error value to a threshold value and determines said power adjustment signal based on said comparison.